Ministry of Communications and Information Technology

Department of Electronics & Information Technology, Standardisation Testing & Quality Certification Directorate

ELECTRONICS REGIONAL TEST LABORATORY (EAST)

TEST REPORT ON DIGITAL SOLAR INVERTER

PAGE 01 OF 4

1.0 SCOPE

1.1 Service Request No.

TE/0090/09-13

1.2 Test Report No.

ERTL(E)/TES/P308/0055/09-13

Date: 22/11/2013

1.3 Requested by

PPS ENVIRO POWER PVT. LTD.

(Name & Address

D97-A,PHASE-1,ROAD-18

of the organisation)

IDA, JEEDIMETIA HYDERABAD 500055

Description,

Identification of the item

Item

DIGITAL SOLAR INVERTER

Make

PPS ENVIRO POWER P. LTD

Model to be tested

SI.No.

PV-UP (E-SERIES)

: SEP-3

Qty.

1

1.4.1 Applicable Spec.of the item(s) tested:

300VA/12V

1.4.2 Characterisation and

Characterisation

: Not applicable /

condition of the item

Condition

: Satisfactory /

Date of item receipt of item 1.5

30/09/2013

Date of start of testing 1.6

13/10/2013

1.6.1 Date of completion of testing

22/11/2013

1.7 Location where testing performed

In house

1.8 Ambient condition during measurement 25 +/- 2°C

75% RH. Max.

Spec. used for testing

IEC:61683

1.9.1 Details of non-standard method followed (if any) NIL

Ministry of Communications and Information Technology

Department of Electronics & Information Technology, Standardisation Testing & Quality Certification Directorate

ELECTRONICS REGIONAL TEST LABORATORY (EAST)

Page No.: 2 of 4

TEST REPORT NO.: ERTL(E) / TES / P308 / 0055 / 09 - 13

TEST REPORT ON DIGITAL SOLAR INVERTER

AS PER IEC 61683 & CUSTOMER'S SPECIFICATION

MAKE: PPS ENVIRO POWER PVT. LTD., MODEL: PV-UP (E-SERIES), CAPACITY: 300 VA, 12 V

SL NO: SEP-03

TEST RESULT:

TEST	TEST/ENVIRONMENT	CL.	QUANTITY		SPECIFICATION	TEST	MEASUREMENT	
NO.		NO.	TESTED	FAILED	LIMITS	RESULTS	UNCERT	
1.0	Output Voltage:- (At 100% Resistive Load)	4.3	1	-	Not Specified.	231.5 Vac	± 0.196	4 Vac
2.0	Output Freqency:- (At 100% Resistive Load)	4.3	1	-	Not Specified.	50.02 Hz.	± 0.000	l Hz.
3.0 3.1	Ripple & Distortion:- THD , at 100% Resistive	4.5	1	<u>-</u>	Not Specified.	2.202 %	± 0.242.	5 %
3.2	Load THD _i at 100% Resistive Load		1	-	Not Specified.	4.83 %	± 0.2423	5 %
4.1	Loss Measurement:- No Load Loss:- Standby Loss:-	7.0	1	« -	Not Specified.	8.17 W.	± 0.0250) W.
5.0	Efficiency Test:-	IEC	I	- -	Not Specified.	0.95 W.	± 0.0250) W.
5.1.1	For unity power factor.:- At 5% of load ie. 15 W (Actualy Tested at 16.1 W)	61683 Table 1	1	-	Not specified.	62.50 %	± 0.0500	W.
	At 10% of load ie. 30 W (Actualy Tested at 29.8 W)		1	<u>2</u> 0	Not specified.	73.93 %	± 0.0500	<i>W</i> .
	At 25% of load ie. 75 W (Actualy Tested at 76.37 W)		1	-	Not specified.	83.14 %	± 0.4846	W.
(At 50% of load ie. 150 W (Actualy Tested at 149.57 W)		1	-	Not specified.	87.52 %	± 0.4846	W.
(At 75% of load ie. 225 W (Actualy Tested at 227.2 W)		1	-	Not specified.	85.69 %	± 0.0024	KW
	At 100% of load ie. 300 W (Actualy Tested at 307.2 W)		1	-	Not specified.	86.15 %	± 0.0024	KW

(A.K.Dhar.) SCIENTIST 'F'

Ministry of Communications and Information Technology

Department of Electronics & Information Technology, Standardisation Testing & Quality Certification Directorate

ELECTRONICS REGIONAL TEST LABORATORY (EAST)

Page No.: 3 of 4

TEST REPORT NO.: ERTL(E) / TES / P308 / 0055 / 09 - 13
TEST REPORT ON DIGITAL SOLAR INVERTER
AS PER IEC 61683 & CUSTOMER'S SPECIFICATION

MAKE: PPS ENVIRO POWER PVT. LTD., MODEL: PV-UP (E-SERIES), CAPACITY: 300 VA, 12 V

SL NO: SEP-03

TEST RESULT:

TEST	TEST/ENVIRONMENT	CL.	QUANTITY		SPECIFICATION	TEST		MEASUREMENT	
NO.		NO.		FAILED	LIMITS	RESULTS		NCERTA	
5.2 5.2.1	For 0.25 power factor.:- At 25% of load ie. 18.75 W	- do -	1	-	Not specified.	-		See No	
5.2.2	At 50% of load ie. 37.5 W		1	.=	Not specified.	-		See No	ote (ii)
5.2.3	At 100% of load ie. 75 W (Actualy Tested at 76.84 W)		I	-	Not specified.	67.81 %	±	0.4846	<i>W</i> .
5.3	For 0.50 power factor.:-	- do -	Necessia terrane						
5.3.1	At 25% of load ie. 37.5 W		1	-	Not specified.	-		See Not	e (iii)
Province Control (At 50% of load ie. 75 W (Actualy Tested at 76.56 W)		1	-	Not specified.	74.72 %	±	0.4846	W.
5.3.3	At 100% of load ie. 150 W (Actualy Tested at 154.85 W)		1	-	Not specified.	75.17 %	±	0.0024	KW
	For 0.75 power factor.:-	- do -							
	At 25% of load ie. 56.25 W (Actualy Tested at 53.75 W)		1		Not specified.	77.04 %	±	0.4846	W.
5.4.2	At 50% of load ie. 112.5 W (Actualy Tested at 115.25 W)		1	-	Not specified.	78.84 %	±	0.4846	W.
5.4.3	At 100% of load ie. 225 W (Actualy Tested at 232.2 W)		1	-	Not specified.	80.06 %	±	0.0024	KW
5.5 5.5.1	For 80% THDi with 0.5 pf.:- At 50% of load ie. 75 W	- do -							
	(Actualy Tested at 75.82 W)		1	-	Not specified.	70.50 %	±	0.4846	W.
5.5.2	At 100% of load ie. 150 W (Actualy Tested at 155.62 W)		1	2	Not specified.	71.17 %	±	0.4846	<i>W</i> .
	Over Load Test At 120% of load ie. 360 W for 30 secs.		-	-	Should withstood	Complied			=======================================

Note:- i) The Inverter capacity is 300 VA, so Full Load Power is 300 KW at unity pf.
ii) Test at 25% & 50% load at 0.25 pf could not be carried out due to facility limitation.

iii) Test at 25% load at 0.5 pf could not be carried out due to facility limitation.

(A.K.Dhar.) SCIENTIST `F`

Ministry of Communications and Information Technology

Department of Electronics & Information Technology, Standardisation Testing & Quality Certification Directorate

ELECTRONICS REGIONAL TEST LABORATORY (EAST)

TEST REPORT ON: DIGITAL SOLAR INVERTER

PAGE 4

OF 4

Test Report No.

ERTL(E)/TES/P308/0055/09-13

Date: 22/11/2013

3.0 **Equipment used**

EQPT_NO				MAKE MO	MODEL		VALID UPTO
	~~~~~	~~~~	~~~		~~		
	100	01.1 . 11.01.11	POWER ANALYSER		PM3300		07/02/2014 01/08/2014
	1232	DIGITAL MU	JLTIMETER	AGILENT TECHNOLO	34401A		01/08/2014

Note: All tests were conducted within the validity period of respective equipment shown above.

### 4.0 Remarks (if any)

NIL

(signature & date)